#### **Technical Specifications**

Ava

Wa

TEL of or discl


Elektroakustik that it is thus defective.

Type Capsule Polar Pattern Frequency Range Sensitivity Impedance Maximum SPL Weight	Dynamic Moving 30mm Moving Cardioid 30Hz – 18kHz 1.4 mV/Pa ±1 0 300 Ohms 140 dB 13.1 oz / 371g	Coil Diaph		THE NOMINEE	
	13.1 oz / 371g (M80) 12.6 oz / 347g (M80-SH) 5.8 oz / 165g (M80-WH)				
Size	7.25" / 184mm length x 1.88" / 48mm diameter (M80) 4.92" / 125mm length x 1.88" / 48mm diameter (M80-SH) 3.56" / 90mm length x 1.88" / 48mm diameter (M80-WH)				
Connector Type	3-pin standard XLR (M80 and M80-SH)				
	90.			metel W	
ailable in many styles				MBD	1
			DRANGE	BLUE	mai curreno
arranty:					
EFUNKEN Elektroakustik, LLC ne (1) year from the original da closes such a defect. This is pr	ate of purchase, and ag	rees to repair o	or replace any part w	hich, under normal in	stallation and use,

This warranty does not apply: (a) to damage caused by use with non-TELEFUNKEN Elektroakustik products; (b) to damage caused by accident, abuse, misuse, flood, fire, earthquake, or other external causes; (c) to damage caused by operating the product outside the permitted or intended uses described by Telefunken | USA; (d) to damage caused by service (including upgrades) performed by anyone who is not a representative of TELEFUNKEN Elektroakustik or a TELEFUNKEN Elektroakustik authorized service provider; (e) to a product or part that has been modified to alter functionality or capability without the written permission of TELEFUNKEN Elektroakustik; (f) to cosmetic damage, including but not limited to scratches and dents.

within 1 year of the original date of purchase, and provided that such examination discloses, in the judgement of TELEFUNKEN

The length of this warranty shall not be extended for any reason without the expressed written consent of TELEFUNKEN Elektroakustik, LLC.



#### 300 Pleasant Valley Road Suite E • South Windsor, CT 06074 www.t-funk.com 860.882.5919

### SUPER CHARGED DYNAMIC MICROPHONE

www.t-funk.com

# **NI80**

## SUPER CHARGED DYNAMIC MICROPHONE

TELEFUNKEN Elektroakustik has created the M80 to give the user a superior alternative to the midrange-laden character of the "industry standard microphone."

Featuring a wider frequency response and higher SPL capabilities the M80 delivers condenser-like performance in a rugged dynamic design, producing a microphone equally suitable for voice, instruments or drums on both stage and in the studio.

Due to its low mass capsule and super thin (yet surprisingly rugged) capsule membrane the M80 presents a wider range of emotion from a live vocal with an intimacy that has been traditionally reserved for studio quality condenser microphones.

The head and capsule assembly has been designed to reduce proximity effect to which nets added low end clarity for vocals, while still providing "strength" and "authority" and an "open," "airy" character without adding danger of upper midrange feedback or "honk."

The M80 also features an American made custom wound impedance matching transformer which is where the magic really takes place. When coupled with our proprietary capsule assembly, the results have won hearts and minds in far less time since its introduction than we ever imagined possible.



Designed to fit into tighter places easier, the M80-SH is a more compact version of the M80, yet retains its same sonic fingerprint. This makes positioning it on drums easier as compared to its full size brother. Also, because of its smaller size (and because of its built-in stand mount), the M80-SH makes a great mic for singing drummers and keyboard players, and for the top of a Leslie cabinet. The M80-SH ships with two different drum mounts (M784 and M785) to allow even greater placement flexibility. It also ships with a 5-meter XLR cable with right angle female connector, allowing it to remain low-profile even with the cable connected.



For those people that don't want to be tied down, we developed the M80-WH, a wireless capsule that threads onto many popular transmitters\*.

TEVAL