




## **Installation Instructions: V7-LP**

## WARNING – To prevent damage to your instrument, carefully follow these installation instructions.

Thank you for selecting the Vibramate V7-LP Mounting Kit for Carved Top Les Paul Style Guitars. This kit has been designed for the simple installation of a Bigsby Original B7 Vibrato on to your guitar without the need to drill holes in your instrument.

- Step 1) Visually inspect the Vibramate mounting plate for alignment. The large mounting holes should align with the existing Stop-Tailpiece inserts on your instrument.
- Step 2) Remove the strings from your guitar. (You may want to cover the instrument with a soft cloth or towel to protect the finish and for added safety during installation.)
- Step 3) Carefully remove the existing Stop-Tailpiece from your guitar. Unscrew and remove both mounting screws. (Save the Stop-Tailpiece and mounting screws in case you decide to remount the original tailpiece.)
- Step 4) Remove the Strap Pin Screw & Strap Pin from the end of your guitar where the Vibrato Tailpiece will mount. Save for securing the Tailpiece-Plate later during installation.
- Step 5) Determine if your mount requires English or Metric mounting screws by carefully testing one of the kit-included screws with your existing inserts.
- Step 6) Place the Vibramate V7-LP Mounting plate on your guitar with the felt-pad side down and the curved front mount edge towards the Tune-O-Matic Bridge. Use Insert-Spacers beneath the Mounting plate if needed. Align the mounting holes with the inserts and secure with correct mounting screws - do not overtighten.
- Step 7) Prepare the Bigsby B-7 Vibrato for mounting by first removing the felt-pads on the front feet of the Vibrato itself.
- Step 8) Align the Vibramate Tailpiece-Plate with the Hinge-Plate on the Bigsby B7 Vibrato. The mounting holes will only fit in one direction and the felt-pads should be facing towards the guitar - do not over tighten. Secure the Vibrato Hinge-Plate to the Vibramate Tailpiece-Plate with the 4 small Round-Head screws included.
- Step 9) Position the Vibrato on to the mounting plate aligning the 2 front mounting holes. Secure the Vibrato with the 2 small Flat-Head mounting screws.
- Step 10) Rotate the Vibrato slightly down towards the back of the guitar so the Vibrato Hinge with the Vibramate Tailpiece-Plate aligns with the existing Strap Pin hole in your guitar. Secure the Tailpiece-Plate to the guitar with your existing Strap Pin & Screw.
- Step 11) Re-string the guitar according to the Vibrato instructions and enjoy!



#### \*Important Notes and Cautions:

- 1) Read all instructions, warnings and disclaimers prior to installation of this product, UE Corporation will not be held responsible for any damage to your instrument.
- 2) Use a qualified repairman or service if you are uncomfortable working on your guitar.
- 3) Some finishes can damage easily from contact with other objects including the
- Vibramate plate and felt pads. Consult a specialist prior to installation if this is a concern. 4) If the inserts in your guitar are loose you can carefully remove them and re-secure with a small amount of wood glue. Allow dry time of 24 hours before installing Vibramate.
- 5) If you are missing hardware or having trouble with the installation of your mounting

### kit please contact our technical service department by e-mail at: info@vibramate.com. Unique Engineering Corporation

po box 126 • ringoes • nj • 08551 Tel: 609-466-8101 • Fax: 609-466-8160

# ©2009 UE Corporation • All Rights Reserved • Vibramate is a registered trademark of UE Corporation Bigsby is a registered trademark of Fred Gretsch Enterprises, Inc. • Les Paul is a registered trademark of Gibson Guitar Co