

DT 150

Dynamic Studio Headphone

Order # 455.970



FEATURES

- Wide frequency response
- High long-term wearing comfort
- Excellent isolation from ambient noise
- Rugged construction
- Extended bass response
- Modular construction for easy servicing

APPLICATIONS

The DT 150 is a dynamic studio headphone for use in broadcasting, film and recording studios and other audio monitoring applications where comfort and performance are primary requirements. Due to its closed design it features excellent ambient noise isolation for reference monitoring.

SUPPLIED ACCESSORY

K 100.07 Straight cable, 3 m,
with 3-pole 1/4" stereo jack
(6.35 mm) Order # 101.753

OPTIONAL ACCESSORIES

K 100.00 Straight cable, 3 m,
bare-ended. Order # 101.170
WK 100.00 Coiled cable, 3 m,
bare-ended. Order # 101.788
WK 100.07 Coiled cable, 3 m,
with 3-pole 1/4" stereo jack
(6.35 mm) Order # 101.826

SPARE PARTS

EDT 150 S Ear pads, soft PVC,
circumaural Order # 931.532
BN 59-58/A Headband pad for DT 150 Order # 377.163

TECHNICAL SPECIFICATIONS

Transducer type Dynamic
Operating principle Closed
Frequency response 5 - 30,000 Hz
Nominal impedance 250 Ω
Nominal SPL 97 dB
T.H.D. $\leq 0.2\%$
Power handling capacity 100 mW
Sound coupling to the ear Circumaural
Headband pressure 4.5 N
Ambient noise attenuation approx. 20 dBA
Weight (without cable) 250 g

(all specifications according to EN 60 268-7)

WIRING DIAGRAM

