

Product code: SZS-C10A-MK2-MIC-MIX-PACK

SubZero 10" Active PA System with Mics, Stands and Mixer

Specifications:

SubZero 10" Active Carpet PA Speaker

- **Type:** Active
- **Cabinet:** Carpet Covered Wood
- **Amplifier:** Class D
- **RMS Power(total):** 250W
- **Peak Power:** 350W
- **Max Power:** 1000W
- **Subwoofer:** 10" 2" VC 40OZ Ferrite
- **Driver:** Piezoelectric Tweeter
- **Impedance (total):** 8Ohm
- **Sensitivity:** 95dB
- **Max SPL Rating:** 122dB
- **Frequency Response:** 60Hz-19kHz
- **AC Power Input:** 220V
- **Fuse Type:** 3.15A
- **Power Consumption:** 300W
- **Accessory:** UK and EU Power Cables
- **N.W:** 11.6kg
- **G.W:** 13kg
- **Product Dimensions:** 34 x 29 x 52 cm
- **Package Dimensions:** 38.5 x 33.5 x 57 cm
- **Product Code:** SZS-C10A-MK2

SubZero SZ-MIX08USB 8-Channel USB Mixer/Interface

- **XLR Mic inputs:** 4
- **Jack Line inputs:** 8 x 1/4"
- **CD Input:** 3.5mm
- **EQ:** ±15dB EQ at 80Hz & 12KHz
- **Headphones:** Out level control
- **RCA:** Input/output
- **Send:** Auxiliary
- **Level indicator:** 4-band LED
- **USB:** USB recording and playing function (stereo output/input only)
- **Frequency Response:** 20Hz to 20kHz
- **Sample Rate:** 16Bit /48K
- **Total Harmonic Distortion:**
- **Mic Input Gain Range:** -20dB to +45dB
- **Line Input Gain Range:** -20dB to +25dB
- **Equalization Range:** HI: ±15dB@12kHz, LOW: ±15dB@80Hz
- **Max Output:** +21dB ±2dB
- **Input Impedance:** Mic: 2.3kΩ balanced, Line: 20kΩ balanced, CD/RCA: 24kΩ unbalanced
- **Phantom Power:** +48VDC (V)
- **Power Supply:** DC12V
- **Dimensions:** W 217mm x D 220mm x H 85mm

Product code: SZS-C10A-MK2-MIC-MIX-PACK

PA Speaker Stands (Pair) With Carry Bag

- **Colour:** Black
- **Material:** Aluminium
- **Dimensions:** W: 1000mm D: 1000mm
- **Height Adjustment:** 1200mm - 2000mm
- **Max Load:** 50kg
- **Top Hat:** 35mm

XLR (M) - Jack Amp/Mixer Cable, 6m

- Heavy Duty XLR Connector
- Noiseless
- Oxygen Free
- Strain Relief Spring Jack
- Pin 2 Positive
- Length: 6m
- Colour: Black