

No.25 Specifications

Type: Closed box, front firing woofer

Drive Unit: 15 in., 100mm long throw, carbon fiber cone with inverted carbon fibre centre cap.

Lower Frequency Response in Room: -6dB at 15Hz

Input Connectors: High Level Neutrik Speakon, Low Level stereo RCA, LFE RCA, LFE XLR

Output Connectors: High Level Neutrik Speakon, LFE RCA, LFE XLR

Gain Control Range: 80 dB

Power Output: 1000 Watts (RMS) Ultra High-Current Power Supply

Phase Switch: Yes, 0 or 180 degrees

Amplifier Type: Next Gen II Class D

Wireless Capability: Yes- REL Longbow™ transmitter [required]. Sold separately.

Protection System

Fully Electronic with SET-SAFE: Yes

DC Fault: Yes

Output Short: Yes

Mains Input Voltage: 220-240 volts, 110-120 volts for certain markets

Fuses: 7 Amp semi delay 230 volts operation

15 Amp semi delay 115 volts operation

Dimensions

W x H x D, Inc. Feet: 22.5 x 18.2 x 26.8 in., (571.5 x 462 x 680.3 mm)

Net Weight: 108 lbs. (49 kg)

Finish: Gloss Piano Black

Supplied Accessories

Mains Lead: Yes

Neutrik Speakon Interconnect 10 Meters Nominal: Yes

Users Manual: Yes

Remote Control: Yes

Batteries (AAA x 2): Yes

Allen Key (2.5mm): Yes